



Fastening Options

Our recycled plastic lumber performs best with the use of #8 or #10 stainless steel flat head and composite deck screws, including popular brands such as Simpson Strong-Tie® or FastenMaster®. Hidden fastening systems, such as EB-TY® biscuits, can be used with our grooved profiles. Refer to the chart shown below for more specific fastening recommendations and color matching options.

Face Fastening (F.F.): Composite Deck Screws or Flat Head Deck Screws Stainless Steel Screws in #8 or #10 Sizes are Recommended		
Stainless Steel Screw Manufacturers (F.F.)	Size	Length
Simpson Strong-Tie: Swan Secure Swaneze Dexter	#8, #10	2-1/2"
FastenMaster Trapease Composite	#8, #10	2-1/2"
Head Cote Composite Flat Head Composite	#8, #10	2-1/2"
Phillips II Plus Composite	#8, #10	2-1/2"
SplitStop Titan 3 - Star Drive Composite	#8, #10	2-1/2"
Color Matching Composite Deck Screws (F.F.) Length: 2-1/2" to 3" Size: #8 or #10	Lumberock Color Name	Screw Color Name
Simpson Strong-Tie Dextter Composite	Chocolate Brown	Brown
Simpson Strong-Tie Dextter Composite	Cedar	IPE
Headcote Composite & Flat Head	Cedar	Cedar #81
Headcote Composite	Putty	Warm Gray #54
Headcote Composite & Flat Head	Redwood	Brown #34
FastenMaster: Trapease I & II	Redwood	Dark Brown
Hidden Fastening System: EBTY Biscuits	Coverage Area 16" O.C.	Coverage Area 24" O.C.
Stock Number: 175-EBTYS, Gap: 3/32" = .09375"	100/Sq./Feet	175/Sq./Ft.
Stock Number: 175-EBTPV, Gap: 1/8" = .125"	100/Sq./Feet	175/Sq./Ft.
Stock Number: 175-EBTYP, Gap: 3/16" = .1875"	100/Sq./Feet	175/Sq./Ft.
Stock Number: 175-EBTYLC, Gap: 1/4" = .250"	100/Sq./Feet	175/Sq./Ft.