



Lumberock® Premium

PORCH BOARD

LET YOUR HOME'S FIRST IMPRESSION BE THE BEST.

Lumberock Premium Porch Boards are the newest addition to our line of long-lasting, low-maintenance plastic decking profiles. These slim, lightweight, tongue-and-groove floor boards easily snap together to create smooth, stylish entryways and porches.

Made with our signature mineral-added HDPE formula, Lumberock Premium Porch Boards offer you a high-performance, environmentally-friendly flooring option with the durability and strength to last a lifetime.

- Quick, Easy Installation
- Fade Resistant
- No Organic Fills or PVC
- Minimal Maintenance
- Cuts and Routers Like Wood
- Mold and Mildew Free
- Will Not Rot, Crack or Splinter
- Resists Stains and Scratches
- Completely Waterproof



Deck | Dock | Rail | Porch

Lumberock® Premium PORCH BOARD



Lumberock Premium Porch Board is great for ceilings, too!

BOARD DETAILS

- Solid extruded, mineral-added polyethylene board
- Size: 3/4" x 4" tongue-and-groove (Actual Dimensions = 0.75" x 3.125")
- Suitable for covered porches
- Colors: Available in all twelve signature Lumberock colors
- Limited Lifetime Warranty

AVAILABLE COLORS



INSTALLATION GUIDELINES

HANDLING & STORAGE

- Always keep Lumberock Premium Porch Board clean prior to installation.
- Note that Lumberock Premium Porch Board is designed to allow for the ends to be trimmed prior to installation should any damage occur during handling or storage.
- Store Lumberock Premium Porch Board out of the sun and lay boards flat. If stored off the ground, support boards every 18".

FASTENERS

We recommend the following fasteners for Lumberock Premium Porch Board:

- Minimum #7 x 2" 305 stainless steel trim head screw with sharp self-drilling tip.
- When using a pneumatic flooring nailer (gun), we suggest using a 2" "L" or "T" cleat hardwood flooring nail.

INSTALLATION DETAILS

- Maximum joist spacing for 90° installation = 12" on center.
- Maximum joist spacing for 45° installation = 8" on center.
- Lumberock Premium Porch Board is embossed with a wood grain finish on one side. Install grain-side up as a walking surface.
- Install first board with the groove facing toward the house if you are running the board parallel to the house. If you are running the board perpendicular to the house, install first board with the groove facing the outside edge of the porch. (Trim groove per perimeter detail notes below.)
- Face-screw or nail one fastener every 12 inches closest to the wall.
- Drive one fastener through the tongue at each joist at a 30° to 45° angle. Fastener should sit approximately 1/16" into the surface of the tongue to allow for the adequate fit of the next board.
- Repeat for all boards, ensuring that all boards fit tightly and utilizing shims where needed to account for variations in framing.
- The final board may require a trim per perimeter detail notes below.
- Face-screw or nail the final board one fastener every 12 inches.

STAIR DETAILS

Maximum joist spacing = 8" on center.

PERIMETER DETAILS

If the first or last board has an exposed edge, rip down to desired width.

CARE & MAINTENANCE

When dirt or debris begin to accumulate on your porch, simply sweep it away, hose it off or lightly wash the boards with soap and water. Any standard household cleaner can be used without harming the (porch board). Occasionally, stubborn dirt can accumulate on the surface but it will not permeate the surface of the board and can be removed with a light pressure washing. We recommend using a maximum of 1800psi with a 20-degree nozzle. Thanks to the non-porous, solid composition of the boards, stains from food and beverages will not adhere to Lumberock Premium Porch Boards and spills are easily washed away.

TOOLS REQUIRED

Lumberock Premium Porch Boards can be installed using the same tools used to install wood porch flooring products.

Please note that Lumberock Premium Decking claims no liability or responsibility for the improper installation of our product. All installations are unique and it is the sole responsibility of the installer to determine specific requirements in regard to each application. We recommend that a licensed architect, engineer or local building official review all designs before installation.

Lumberock® Premium Decking

885 Church Road, Elgin, IL 60123

Visit lumberock.com or call 800-480-2327

Find us on Facebook at www.facebook.com/lumberock

A product of
Engineered Plastic Systems, LLC

©2022 Lumberock® Premium Decking